

# Evolve Range Benches – Cloakroom Seating Manufactured by:

*ESE Direct Ltd*, Wensum Works, 150 Northumberland Street, Norwich, Norfolk, NR2 4EE

Telephone: 01603 629956 – Fax: 01603 630113 – Email: [sales@esedirect.co.uk](mailto:sales@esedirect.co.uk)

Website: [www.benchura.co.uk](http://www.benchura.co.uk)



## N10 - Specification:

### 'DS...X' - Evolve Duo Cloakroom Bench with NO top shelf:

**Dimensions:** 800mm deep x 1750mm high, 450mm high seat as standard (Junior – Infant sizes available). 1m - 1.5m - 2m or 2.5m - 3m long with a third upright.

**Leg frames:** Constructed of 30mm x 30mm box section with mitred joints, ground / polished then powder coated to finish, pre-drilled to take seat frames, and shoe rack (if required) with plastic feet as standard. Floor fixing cleats or adjustable feet available as options.

**Seats:** One per side constructed using a powder coated 30x30 formed angle support framework for additional strength, onto which 3x 75mm x 25mm Ash hardwood slats are factory fitted.

**Hat and Coat rail:** Positioned at 1600mm high, constructed of 75mm x 25mm Ash hardwood, both sides of which Satin Anodised Aluminium two prong coat hooks are fitted.

1m = 10 hooks - 1.5m = 14 hooks - 2m = 20 hooks - 2.5m = 24 hooks - 3m = 32 hooks

## OPTIONS:



**Mesh Shoe Racks:** 30x30 formed angle support framework into which 50mm x 25mm mesh is fitted, simply bolts into the legs under the bench seat units at 150mm centres from the floor.

**Back Rests:** 75mm x 25mm Ash hardwood rounded on all four edges and bolted to steel mounting brackets on the uprights.

## FINISH:

**Colours:** Stocked in Blue (RAL5002) and also available in 5 additional colours - Silver (Gloss) - Yellow (RAL1018) - Red (RAL3020) - Grey (BS18B25) - Black (RAL9005).

**Ash hardwood slats:** Sourced via FSC (Forestry Stewardship Council) approved agents who only harvest timber from responsibly managed and sustainable forests. Members of TTF (Timber Trades Federation) with systems in place to ensure only legal timber handled. Ash is cut to size, profiled with a 6mm round on the long edges, sanded, cleaned and finished with 2 part cellulose ac lacquer with 30% sheen level.

**Steel / metal legs and seat support frames:** Welded in jigs for dimensional consistency, welds ground flush and all steel cleaned using a vapour immersion degreaser, then electro statically epoxy polyester powder coated to approx 60-80 microns, baked in an industrial oven and wrapped for protection during transport.

**Zinc Plating:** If the bench seats are for use in wet conditions or where there is exposure to chlorine / bromine etc, please ensure you request Zinc Plating (additional cost applicable).

**Note:** For high humidity, regularly very wet areas, external or pool side applications we would recommend our Stainless Steel range.